4			₩ Ope V	ATTORNEY'S DOCKET NUMBER					
ORM PT	00)		T OF COMMERCE PATENT AND TRADEMARK OFFICE						
	TRA	ANSMITTAĽ LETTER	TO THE UNITED STATES	990.1246					
		DESIGNATED/ELECT	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR						
		CONCERNING A FILIN	1 09/719029						
		ONCERNING A FILIT	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED					
INTEK		CT/F199/00458	May 27, 1999	June 5, 1998					
TITLE	OF IN	VENTION		THE					
EQUI	IPME	ENT AND METHOD IN A	PAPER OR BOARD MACHINE FOR	MIXING OF FRESH STOCK AND OF					
WAT	ER F	OR DILUTION OF FRES	H STOCK						
APPLI	CANT	(S) FOR DO/EO/US							
Jouni	i RAI	IKOMAA et al.							
Applic	cant he	erewith submits to the United St	tates Designated/Elected Office (DO/EO/US) t	he following items and other information:					
1.	\boxtimes	This is a FIRST submission of	items concerning a filing under 35 U.S.C. 371	I.					
2.			QUENT submission of items concerning a fili						
3.	K21	The construction of the basis participal examination procedures (35 U.S.C. 371(f)) at any time rather than delay							
		examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.							
4.	\boxtimes			e 19th month from the earliest claimed priority date.					
5.	\boxtimes		plication as filed (35 U.S.C. 371 (c) (2))	d 10					
			th (required only if not transmitted by the Inte	rnational Bureau).					
1		b. \square has been transmitted	by the International Bureau.	origina Office (PO/US)					
			application was filed in the United States Rec						
6.			nal Application into English (35 U.S.C. 371(c))	(2)).					
7.	×	A copy of the International Sea	arch Report (PC1/18A/210). he International Application under PCT Articl	e 19 (35 U.S.C. 371 (c)(3))					
8.	\bowtie		ine international Application under I CT Article in its first indicate in its international Application under I CT Article in its internation under I CT Article in its internat						
1			d by the International Bureau.	emational Bureau).					
1				adments has NOT expired					
			c. have not been made; however, the time limit for making such amendments has NOT expired						
			d. Mean have not been made and will not be made.						
9.		A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).							
10.	□ r≈1								
11.		A copy of the International Preliminary Examination Report (PCT/IPEA/409). A translation of the annexes to the International Preliminary Examination Report under PCT Article 36							
12.	L.J	(35 U.S.C. 371 (c)(5)).							
l 14	tems 1	3 to 20 below concern docum	ent(s) or information included:						
13.			atement under 37 CFR 1.97 and 1.98.						
14.		An assignment document for a	recording. A separate cover sheet in compliance	ce with 37 CFR 3.28 and 3.31 is included.					
15.	\boxtimes	A FIRST preliminary amendr							
16.		A SECOND or SUBSEQUE							
17.		A substitute specification.							
18.		A change of power of attorney and/or address letter.							
19.	\boxtimes	Certificate of Mailing by Express Mail							
20.	\boxtimes	Other items or information:							
	Letter Re Priority								
		Submission of Application f	or Filing Date Without Declaration						
Į.		X							
				•					

· J. V

528 Rec'd PCT/PTO 0 5 DEC 2000

U.Ş. APPLICATION NOTICKNOWN, SEIDTOFD 9 INTERNATIONAL APPLICATION NO PCT/F199/00458						ATTORNEY'S DOCKET NUMBER 990.1246					
21.	The fol	lowing fees are submitted	d:.					CALCUI	LATIONS	PTO USE ONLY	
BASIC ⊠	Neither inter international	L FEE (37 CFR 1.492 (mational preliminary exa search fee (37 CFR 1.44 ional Search Report not p	mination 5(a)(2)	n fee (37 CFR 1.482 paid to USPTO	•	\$97	70.00		-	-	
	International USPTO but	preliminary examination Internation Search Repor	n fee (37 t prepar	CFR 1.482) not paged by the EPO or J	aid to PO	\$84	10.00				
				00.00							
International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4)						70.00					
	International and all claim	preliminary examination s satisfied provisions of	ı fee paid PCT Art	d to USPTO (37 Cl ticle 33(1)-(4)	FR 1.482)	\$9	6.00				
	10	ENTER APPR	OPRL	ATE BASIC I	FEE AMO	DUNT =	:	\$1	,000.00		
Surcha month	arge of \$130.0 s from the ear	00 for furnishing the oath liest claimed priority da	or decla te (37 Cl	ration later than FR 1.492 (e)).	20) 🛚 3	0		\$130.00		
CL.	AIMS	NUMBER FILE	.D	NUMBER E	XTRA	RATE					
Total c			20 =	0		x \$18.0			\$0.00		
	endent claims		3 =	0		x \$80.0)()		\$0.00 \$0.00		
Multi	pie Dependen	t Claims (check if applic		ABOVE CA	LCULAT		_	\$1	,130.00		
Reduc must a	tion of 1/2 for llso be filed (1	filing by small entity, in Note 37 CFR 1.9, 1.27, 1	f applica	ble. Verified Smal	Il Entity State				\$0.00		
	7				SUBT	FOTAL	=	<u>\$1</u>	,130.00		
		30.00 for furnishing the liest claimed priority da					0 +		\$0.00		
				TOTAL NA	TIONAL	FEE	=	\$1	,130.00	 	
		e enclosed assignment (3 appropriate cover sheet (\$0.00		
				TOTAL FEE	ES ENCL	OSED			,130.00		
								Amount t refun	ded	\$ 	
								char	ged S	\$	
×	A check in	the amount of \$1,130.0	0	to cover the above	ve fees is enc	losed.					
		ge my Deposit Account I c copy of this sheet is end		in th	he amount of		to cover the above fees.				
×		issioner is hereby authori Account No. 50-05		harge any fees which A duplicate copy o	-	• ′	redit ar	ıy overpayı	ment		
NOTE 1.137(C: Where an a) or (b)) mu	appropriate time limit of the state of the s	under 3′ to restor	7 CFR 1.494 or 1.4 re the application	495 has not b to pending s	een met, a tatus.	petitio		· 🕳		
SEND	ALL CORRE	ESPONDENCE TO:					(PAUL	J. H166 INS	
STEINBERG & RASKIN, P.C. 1140 Avenue of the Americas, 15th Floor						URE			, Mr. 44,15 L		
New '	New York, New York 10036-5803 Martin G.							Raskin			
						NAME			1000	-	
						25,642					
REGISTRATION December 5,					RATIO	ON NUMBER					
					er 5, 2	2000					
						DATE					

990.1246

UNITED STATES PATENT AND TRADEMARK OFFICE

Re:

Application of:

Jouni RAHKOMAA et al.

Serial No.:

Not yet known

Filed:

Simultaneously

For:

EQUIPMENT AND METHOD IN A PAPER OR BOARD MACHINE FOR MIXING OF FRESH STOCK AND OF WATER FOR DILUTION OF FRESH

STOCK

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

December 5, 2000

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE SPECIFICATION:

Please amend the specification as follows. (reference is made to the lines as numbered).

Page 1, line 6, insert -- FIELD OF THE INVENTION --;

line 10, insert -- BACKGROUND OF THE INVENTION --; and

line 15, insert -- OBJECTS AND SUMMARY OF THE INVENTION--.

Page 2, before line 1, insert -- BRIEF DESCRIPTION OF THE DRAWINGS ---.

Page 3, line 5, insert -- **DETAILED DESCRIPTION OF THE INVENTION**--; line 13, after "pipe", insert --13--; line 16, change "the tank 100", first occurrence to --a wire pit tank 10--; line 16, change "tank 100", second occurrence to --wire pit tank 10--; and line 26, after "outside", insert --of the circumference--.

Page 4, line 5 to line 6, change "pit 10. Into" to --pit 10 and into--; line 6, change "wire pit 10, besides" to --wire pit 10. In addition to the--; and line 9, after "L₃" insert --(as seen in Fig. 1D)--.

Page 6, after line 7, insert:

In the following, the patent claims will be given, and the various details of the invention can show variation within the scope of the inventive idea defined in the claims and differ even to a considerable extent from the details stated above by way of example only. As such, the examples provided above are not meant to be exclusive and many other variations of the present invention would be obvious to those skilled in the art, and are contemplated to be within the scope of the appended claims.—

IN THE DRAWINGS

In Fig. 1A, reference numeral "100" has been changed to reference numeral "10" to reflect the changes made to page 3 of the specification and to remove an ambiguity in the numbering of the elements. The change has been made in red ink.

IN THE CLAIMS:

Please amend the claims as follows.

(Amended) An equipment in a paper or board machine for mixing fresh stock
 (M) with water (V) used for dilution of the fresh stock, [characterized in that] comprising:

at [the] <u>a</u> point of mixing (K) of the dilution water (V), <u>passed from a dilution water pipe</u> (11), and the fresh stock (M), <u>passed from [the] a fresh stock pipe</u> (13), there is at least one such pipe portion [as comprises] <u>having</u> a wave-shaped form in its connection in [the] <u>a</u> cross-section of the pipe.

Claim 2, line 1, change "characterized in that" to --wherein--.

Claim 3, line 1, change "or 2, characterized in that" to --wherein--; line 2, before "comprises", insert --further--; and line 2, change "the", first occurrence, to --a--.

4. (Amended) An equipment as claimed in [any of the preceding claims, characterized in that] <u>claim 1</u>, <u>wherein</u> the <u>dilution water</u> pipe (11) [is provided with] <u>further comprises:</u>

a wave-shaped form on [its] a wall face thereof.

Claim 5, line 1, change "characterized in that" to --wherein--; and line 2, change "the", first occurrence, to --an--.

Claim 6, line 1, change "any of the preceding claims, characterized in that" to --claim 3, wherein--.

Claim 7, line 1, change "any of the preceding claims, characterized in that" to --claim 3, wherein--.

Claim 8, line 1, change "characterized in that" to --wherein--; line 2, change "the", second occurrence, to --a--; line 2, delete "pipe", second occurrence; and line 2, after "portion", insert --of pipe--.

9. (Amended) An equipment as claimed in [any of the preceding claims, characterized in that] claim 1, wherein the [duct] white water pipe (11) further comprises:

a pump (P) placed after the mixing point (K) of the white water, fresh stock, and \underline{a} circulation water in view of passing said materials into [the] \underline{a} headbox (100) of the paper/board machine.

Claim 10, line 1, change "any of the preceding claims, characterized in that" to --claim 1, wherein--; and

line 2, change "the", second occurrence, to --a--.

```
Claim 11, line 1, change "characterized in that" to --wherein--; line 2, change "the", second occurrence, to --a--; line 2, delete "(100)"; and line 2, change "the", third occurrence, to --a--.
```

12. (Amended) A method in a paper or board machine for mixing fresh stock (M) with water (V) used for dilution of the fresh stock, [characterized in that] comprising the step of:

forming secondary vortexes at [the] a point of mixing (K) of the <u>dilution</u> water (V) [used for dilution of fresh stock (M)], passed from a <u>dilution</u> water pipe (11), and the fresh stock (M), passed from [the] a <u>fresh stock</u> pipe (13), [secondary vortexes are formed, which] <u>said vortexes</u> [are] <u>being</u> formed by means [of a wave-shaped face form of] <u>at least one of said pipes</u> [the pipe] <u>having at least an end portion with a wave-shaped cross-section</u>.

Claim 13, line 1, change "characterized in that" to --wherein--.

Claim 14, line 1, change "characterized in that" to --wherein--;

line 2, change "the", first occurrence, to --a--;

line 2, delete "(100)"; and

line 2, change "the", second occurrence, to --a--.

Please add the following new claims.

--15. An equipment for the improved mixing and diluting of a fresh stock (M) with a white water (V) in a paper or board machine, comprising:

a white water pipe (11) for conducting said white water (V);

a fresh stock pipe (13) structured and arranged to feed said fresh stock (M) coaxially into said white water pipe (11) at a mixing point; and

at least one of said white water pipe (11) and said fresh stock pipe (13) having at least a portion which has a transverse cross-section that is wave-shaped, said portion being located at said mixing point between said fresh stock (M) and said white water (V), whereby said wave-shape produces secondary vortexes in said flow of fresh stock and flow of white water in order to enhance the mixing and diluting of said fresh stock flow with said white water flow.

16. The equipment according to claim 15, further comprising:

a return circulation water pipe (12) is structured and arranged to coaxially conduct a return circulation water (O), through said white water pipe (11), to said mixing point between said fresh stock (M) and said white water (V); and

wherein said fresh stock pipe (13) is structured and arranged to coaxially conduct said fresh stock (M) into said return circulation water pipe (12), to said mixing point between said fresh stock (M) and said white water (V).

- 17. The equipment according to claim 15, wherein said wave-shape is formed on an inner surface of said white water pipe, wherein said wave-shape comprises a plurality of spaced form pieces extending radially inward from said inner surface of said white water pipe.
- 18. The equipment according to claim 17, wherein said form pieces have a curved cross section.
- 19. The equipment according to claim 16, wherein said fresh stock pipe (13), structured and arranged coaxially within said return circulation water pipe (12), is provided with said wave-shape formed along an inner circumferential surface and an outer circumferential surface thereof, whereby said return circulation water (O), conducted through said return circulation water pipe (12), is conducted over said wave-shape formed along said outer circumferential surface of said fresh stock pipe (13) and whereby said fresh stock (M), conducted through said fresh stock pipe (13), is conducted over said wave-shape formed along said inner circumferential surface of said fresh stock pipe (13), thereby producing secondary vortexes in said return circulation water (O) and said fresh stock (M).

20. The equipment according to claim 16, wherein said return circulation pipe (12), structured and arranged coaxially within said white water pipe (11), is provided with said waveshape formed along an inner circumferential surface and an outer circumferential surface thereof, whereby said return circulation water (O), conducted through said return circulation water pipe (12), is conducted over said wave-shape formed along said inner circumferential surface of said return circulation pipe (12) and whereby said white water (V), conducted through said white water pipe (11), is conducted over said wave-shape formed along said outer circumferential surface of said return circulation pipe (12), thereby producing secondary vortexes in said return circulation water (O) and said white water (V).--

- BY// BUDA Pare J. H166 WS Rec. No. 44,152

REMARKS

The specification has been amended to include section headings at appropriate locations.

In Fig. 1A, reference numeral "100" has been changed to reference numeral "10" to reflect the changes made to page 3 of the specification and to remove an ambiguity in the numbering of the elements. The change has been made in red ink.

Claims 1-14 as filed in the corresponding International Patent Application have been amended to correct minor informalities and to remove multiple dependencies in order to reduce the filing fee. New claims 15-20 have been added which are directed to embodiments disclosed in the original specification. No new matter has been added.

The invention is new, useful and non-obvious.

Respectfully submitted,

STEINBERG & RASKIN, P.C.

Martin G. Raskin

Reg. No. 25,642

Encl.

Steinberg & Raskin, P.C. 1140 Avenue of the Americas New York, New York 10036

(212) 768-3800

WO 99/64666

PCT/F199/00458

Equipment and method in a paper or board machine for mixing of

fresh stock and of water for dilution of fresh stock

5

The invention concerns an equipment and a method in a paper or board machine for mixing fresh stock used for manufacture of paper or board with water used for dilution of the fresh stock.

10

From the prior art, a solution of equipment is known in which fresh stock and a return circulation are passed into a narrowing duct after the wire pit in a paper or board machine. An essential feature of the system is good mixing of fresh stock, white water, and the return circulation.

15

20

In an attempt to obtain good mixing of the white water of the short circulation and of fresh stock in a paper/board machine, in the present patent application it is suggested that, in the area in the duct after the wire pit in which the fresh stock is introduced, at least one duct comprises, on its face, a duct form that is wave-shaped in a cross-section perpendicular to the longitudinal axis of the flow duct. Said wave-shaped duct form produces secondary vortexes in the flow, which vortexes result in efficient mixing of the flows.

25

The equipment in accordance with the present invention is characterized in that, at the point of mixing of the dilution water and the fresh stock passed from the pipe, there is at least one such pipe portion as comprises a wave-shaped form in its connection in the cross-section of the pipe.

30

The method in accordance with the invention is characterized in that, at the point of mixing of the water used for dilution of fresh stock and the fresh stock passed from the pipe, secondary vortexes are formed, which are formed by means of a wave-shaped face form of the pipe.

The invention will be described in the following with reference to some preferred embodiments of the invention illustrated in the figures in the accompanying drawings, the invention being, yet, not supposed to be confined to said embodiments alone.

5

10

Figure 1A illustrates a common embodiment of the invention, in which a water in general, which has been meant for dilution of stock, and a high-consistency stock are mixed while making use of a wave-shaped pipe form.

Figure 1B is a sectional view taken along the line IV - IV in Fig. 1A on an enlarged scale.

15

Figure 1C is an illustration of principle of the short circulation in a paper/board machine, in which white water that has been recovered as retention is passed into the wire pit, white water being passed from the bottom of the wire pit as a return circulation into the headbox.

20

Figure 1D is an illustration on a larger scale of an arrangement of equipment in accordance with the invention in which feed pipes of stock and of the return circulation are passed into connection with the white water passed from the bottom portion of the wire pit.

Figure 2A shows a first embodiment of the invention, in which the wave-shaped form has been formed onto the inner wall of the pipe 11 connected with the wire pit.

25

Figure 2B is a sectional view taken along the line I—I in Fig. 2A.

Figure 3A shows a second embodiment of the invention, in which the wave shape has been formed onto a pipe 13 passed in the interior of the pipe 12.

30

Figure 3B is a sectional view taken along the line II—II in Fig. 3A.

Figure 4A shows an embodiment of the invention, in which the wave-shaped form has been formed onto the pipe 12.

Figure 4B is a sectional view taken along the line III—III in Fig. 4A.

5

10

15

20

Fig. 1A illustrates the commonest embodiment of the invention, in which the water V used for dilution of fresh stock M is passed through the pipe 11, and the highconsistency fresh stock M is passed through the pipe 13. At the end of the pipe 13 and after said end, the high-consistency stock M and the water V used for dilution of the stock are mixed with each other owing to the wave formation in accordance with the invention at the end of the pipe 13. In the embodiment shown in Fig. 1A, the wave form extends both to the interior of the pipe 13 and to the outer face of the pipe, in which case the mixing of the water V used for dilution of the fresh stock M with the fresh stock M is efficient. The water passed along the pipe 11 and used for dilution of the stock is favourably white water, which is passed, in the way shown in Fig. 1A, from the tank 100. As is shown in the figure, the tank 100 is a deaeration tank of the short circulation in a paper or board machine, into which tank the white water V is passed from a separate intermediate tank. Thus, in the commonest embodiment of the invention, by means of the wave-shaped pipe construction 13, in general, the high-consistency fresh stock M and the water V that dilutes said stock are mixed with each other efficiently, and the dilution water favourably consists of the white water of the short circulation in the paper/board machine.

25

Fig. 1B is a sectional view taken along the line IV—IV in Fig. 1A. As is shown in the figure, the line of supply of the high-consistency stock, preferably a pipe 13, is provided with a wave formation at its end. The waves extend both inside and outside the pipe 13, in which case they act both upon the fresh stock M flowing in the pipe 13 and upon the stock dilution water V, favourably white water, flowing outside the pipe 13.

30

Fig. 1C is an illustration of principle of the use of the white-water pit of the short circulation in a paper or board machine in collecting of retention waters and in

recycling of fibrous white water, in which connection the fresh stock M and the water O of the return circulation are passed into connection with the white water V and in which construction, further, the combined mixed flow is passed from the wire pit 10 into connection with the headbox 100 of the paper or board machine. As is shown in Fig. 1C, the white waters are passed from the wire into the wire pit 10. Into the duct 11 placed at the bottom of the wire pit 10, besides white water V from the wire pit 10, the water O of the return circulation from the tank F and the fresh stock M from the stock tank S are also passed. By means of a pump P, the combined flow $L_1 + L_2 + L_3$ is passed further into the headbox 100.

10

15

5

At the bottom of the wire pit, in accordance with the invention, the white water is mixed with the fresh stock and with the water of the return circulation, which water is, for example, a bypass flow circulation from the headbox or an accept from the second stage of vortex cleaning. The sequence of consistencies is as follows. The highest consistency is that of the high-consistency stock. The next consistency is that of the water from the return circulation, and the lowest consistency is that of the white water (white water < return circulation < high-consistency stock).

Fig. 1D shows an equipment in accordance with the invention, in which, in the way

indicated by the arrow L₁, the fibrous water is passed from the white-water pit 10 back to circulation into the pipe 11. Into the pipe 11, also fresh stock M is passed from the pipe 13, and the water O of the return circulation is passed from the pipe 12. The pipe 12 has been passed into the interior of the pipe 11 in an area in which the pipe 11 is curved and its cross-sectional flow area becomes narrower. Through the pipe 12, the return circulation, i.e. the water O of the return circulation, is passed (arrow L₂) into connection with the white water V. Centrally in the interior of the pipe 12, there is the pipe 13. The pipe 13 has been passed coaxially in the interior of the pipe 12. Through the pipe 13 (arrow L₃) the fresh stock M is passed into connection with the water O of the return circulation and with the white water V passed from the wire pit 10. Thus, in the narrowing flow passage in the pipe 11, in the area K, the stock M, the return circulation water O, and the white water V are

mixed. As is shown in the figure, the pump P produces suction in the pipe 11, and

by means of the pump P the combined flow $L_1 + L_2 + L_3$ of the components V, M, O is passed further into connection with the headbox 100 of the paper/board machine.

In order that the mixing of the stock M and of the return circulation water O and of the white water V should be as efficient and complete as possible, in the area K of mixing of the flows L₁, L₂ and L₃, at least one of the pipes 11, 12 or 13 is provided with a wave-shaped face form in a cross-section perpendicular to the longitudinal axis of the flow duct. Said wave-shaped face form produces what is called secondary vortexes, which promote the mixing together of the flows L₁, L₂ and L₃.

Fig. 2A is a longitudinal sectional view of the mixing area K and of a first preferred embodiment of the invention. Fig. 2B is a sectional view taken along the line I - I in Fig. 2A. Figs. 2A and 2B show an embodiment in which the pipe 11 has been provided with form pieces a_1, a_2, a_3, \ldots , whose outer circumference becomes narrower in wedge shape, which have been fitted on the inner face of the pipe 11, and which have been further shaped so that, as shown in the cross-sectional view, the maximal height of the wedge part a_1, a_2, a_3, \ldots that produces the wave shape, in the middle of the wedge part a_1, a_2, \ldots , is placed in the area of the end of the pipe 12 that passes the water O of the return circulation. The pipe 13 that passes the stock M projects further from the interior of the pipe 12.

15

20

25

30

Fig. 3A is a longitudinal sectional view of a second embodiment of the invention. Fig. 3B is a sectional view taken along the line II—II in Fig. 3A.

In the embodiment shown in Figs. 3A and 3B, the wave shape has been formed onto the central pipe 13 fitted inside the pipe 12. The pipe 13 projects from the pipe 12. Thus, secondary vortexes are produced both in the flow L_2 of the return circulation water O inside the pipe 12 and in the flow L_3 of fresh stock M inside the pipe 13. Thus, by means of the wave-shaped face of the pipe 13, an effect that produces secondary vortexes is applied both to the return circulation water O flowing in the pipe 12 and to the stock M that flows in the pipe 13.

Fig. 4A is a longitudinal sectional view of a third preferred embodiment of the invention. Fig. 4B is a sectional view taken along the line III—III in Fig. 4A.

Figs. 4A and 4B show an embodiment of the invention in which the wave shape has been formed onto the flow pipe 12 so that the wave shape acts upon the flow L₁ of white water V in the pipe 11 and upon the flow L₂ of the return circulation water O in the pipe 12.

PCT/F199/00458

7

Claims

5

- 1. An equipment in a paper or board machine for mixing fresh stock (M) with water (V) used for dilution of the fresh stock, **characterized** in that, at the point of mixing (K) of the dilution water (V) and the fresh stock (M) passed from the pipe (13), there is at least one such pipe portion as comprises a wave-shaped form in its connection in the cross-section of the pipe.
- An equipment as claimed in claim 1, characterized in that the dilution water (V)
 consists of white water.
 - 3. An equipment as claimed in claim 1 or 2, characterized in that the equipment comprises a pipe (12) for passing the return circulation water (O) to the mixing point (K) of fresh stock (M) and white water (V), and that the pipe (13), through which the stock (M) is passed, has been passed coaxially in the interior of the pipe (12).
 - 4. An equipment as claimed in any of the preceding claims, **characterized** in that the pipe (11) is provided with a wave-shaped form on its wall face.
- 5. An equipment as claimed in the preceding claim, characterized in that the wave shape on the inner face of the pipe (11) has been produced by means of form pieces (a₁,a₂,a₃...), which form pieces are of curved cross-section and which have been fitted at a distance from one another on the circumferential measure of the pipe (11) on the inner face of the pipe (11).

25

30

15

6. An equipment as claimed in any of the preceding claims, characterized in that the pipe (13), which is placed in the interior of the pipe (12), is provided with a wave-shaped face form, in which case the return circulation water (O) that is passed in the pipe (12) is confined by the wave-shaped outer shape of the pipe (13), and the stock (M) that is passed in the pipe (13) is confined by the wave-shaped inner shape of the pipe (13).

PCT/FI99/00458

5

15

- 7. An equipment as claimed in any of the preceding claims, **characterized** in that the pipe (12), through which the return circulation water (O) is introduced in the pipe (11), is provided with a wave shape, whose form is provided both on the inner face and on the outer face of the pipe, in which connection both the white water (V) flowing in the pipe (11) and the return circulation water (O) passed in the pipe (12) are confined by said wave shape.
- 8. An equipment as claimed in the preceding claim, **characterized** in that the pipe (12) and the pipe (13) have been passed through the curved pipe portion (11) placed below the white-water pit (10) so that the pipes (12 and 13) have been passed through the wall of the pipe (11), and that the pipe (13) projects from the end of the pipe (12), and that the pipe (13) is placed centrally inside the pipe (12).
 - 9. An equipment as claimed in any of the preceding claims, **characterized** in that the duct (11) comprises a pump (P) placed after the mixing point (K) of white water, fresh stock, and circulation water in view of passing said materials into the headbox (100) of the paper/board machine.
- 10. An equipment as claimed in any of the preceding claims, characterized in that the pipe (11) becomes narrower in the flow direction of the flow $(L_1 + L_2 + L_3)$.
 - 11. An equipment as claimed in claim 2, characterized in that the white water (V) that is used as the dilution water is passed from the deaeration tank (100) of the short circulation in the paper/board machine.

25

30

12. A method in a paper or board machine for mixing fresh stock (M) with water (V) used for dilution of the fresh stock, **characterized** in that, at the point of mixing (K) of the water (V) used for dilution of fresh stock (M) and the fresh stock (M) passed from the pipe (13), secondary vortexes are formed, which are formed by means of a wave-shaped face form of the pipe (11 and/or 12 and/or 13).

WO 99/64666 PCT/FI99/00458

9

- 13. A method as claimed in claim 12, characterized in that white water is used as the dilution water (V).
- 14. A method as claimed in the preceding claim, characterized in that the white water is passed from the deaeration tank (100) of the short circulation of the white water in the paper/board machine.







INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶:

(11) International Publication Number:

WO 99/64666

D21F 1/08

(43) International Publication Date:

16 December 1999 (16.12.99)

(21) International Application Number:

PCT/FI99/00458

A1

(22) International Filing Date:

27 May 1999 (27.05.99)

(30) Priority Data:

981286

5 June 1998 (05.06.98)

FI

(71) Applicant (for all designated States except US): VALMET CORPORATION [FI/FI]; Panuntie 6, FIN-00620 Helsinki (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RAHKOMAA, Jouni [FI/FI]; Ketokuja 3, FIN-33730 Tampere (FI). SOINI, Sakari [FI/FI]; Kermisenkuja 5 C 16, FIN-31400 Somero (FI).

(74) Agent: FORSSÉN & SALOMAA OY; Yrjönkatu 30, FIN-00100 Helsinki (FI).

(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


Published


With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

In English translation (filed in Finnish).


(54) Title: EQUIPMENT AND METHOD IN A PAPER OR BOARD MACHINE FOR MIXING OF FRESH STOCK AND OF WATER FOR DILUTION OF FRESH STOCK






(57) Abstract

The invention concerns an equipment and a method in a paper or board machine for mixing fresh stock (M) with water (V) used for dilution of the fresh stock. At the point of mixing (K) of the dilution water (V) and the fresh stock (M) passed from the pipe (13), there is at least one such pipe portion as comprises a wave-shaped form in its connection in the cross section of the pipe.










FIG. 1D





the specification of which (check one) is attached hereto.

Docket No.: 99

U.S.A. **DECLARATION AND POWER OF ATTORNEY**

As the below named inventor, I hereby declare that: My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: Equipment and method in a paper or board machine for mixing of fresh stock and of water for dilution of fresh stock


x was	filed onDecember 5.	2000 as Application Seria	I No0 <u>9/701</u> ,	,029 and
was amended on	12/05/00 (if ap	plicable). I Hereby authorize	and request	my attorney,
Steinberg & Raski	in, P.C. of 1140 Avenue	of the Americas, New York	New York 1	0036 to insert
	application number wh			
		and understand the contents		
specification, inclu	iding the claims, as am	ended by any amendment re	merred to spi	ove.
		all information which is know ined in Title 37, Code of Fed		
are parenteently a	, 			•
		r Title 35, United States Cod		
		nt or inventor's certificate list		
identified below as	ny foreign and/or provis	ional application for patent o	ir inventor's i	certificate
having a filing date	e before that of the app	lication on which priority is c	laimed.	-
PRIOR APPLICA	TION(S)		Priority (claimed
981286	Finland	June 5, 1998	х	
	, ,,, , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	2	Yes	No

I Hereby claim the benefit under Title 35, United States Code, §120 of any United States applications(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, §1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application.

PCT/FI99/00458

May 27, 1999

pending



And I hereby appoint

Martin G. Raskin, Registration No. 25,642,

Harold D. Steinberg, Registration No. 17,255,

Joshua L. Raskin, Registration No. 40, 135,

Anthony L. Meola, Registration No. <u>P44,936</u>,

Jason E. Hardiman, Registration No. 36,157



my attorneys, with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith; correspondence address:

STEINBERG & RASKIN P.C.

1140 Avenue of the Americas

New York, N.Y. 10036;

Telephone: (212) 768-3800; Fax: (212) 382-2124.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or Imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of first

inventor

Jouni RAHKOMAA

000

Inventor's signature

Date

<u>Tampere,</u> Finland Residence

Citizenship

Post Office Address

Finnish

12.

Ketokuja 3, FIN-33730 Tampere, Finland

Full name of second

inventor

Sakari SOINI

Inventor's signature

12.12.2000 Date

Residence

Finnish

Citizenship Post Office Address Somero, Finland

Kermisenkuja 5 C 16, FIN-31400 Somero, Finland